


TECHNICAL SPECIFICATION SHEET

Hooklift container (Roll-on-roll-off) 24 cbm (Height 1750 mm)

Smoothline type, for solid waste, recyclables and light construction materials

Fully engineered roll-on-roll-off-containers, German design, DIN compliant with all related safety features. Made on purpose as light weight container from extra high grade steel, to accommodate higher pay load. Bended and rounded side wall and bottom steel sheets, for optimum waste discharge and highest stability. Top-lock device at rear doors. Work Safety door locking device at the side. Heavy duty rollers made from special sturdy polyamid or steel. Net hooks for tarpaulin covers included. Optional ladder at the front. Available in all sizes and in various other designs, with and without cover, for specific applications, too.





Pictures and drawings: The picture on display is for illustrative purposes only; minor model changes reserved.

Pictures and drawings: The picture on display is for illustrative purposes only; minor model changes reserved.	
Specifications	
Length 5750 x Width 2400 x Height 1750 mm - 24 cubic meter	
approx. 2,700 kg	
Manufactured according to DIN 722 30 Part 1 or to local standards	
Smoothline - Two convex side panels;	
Bottom 5 mm, sidewalls, front and door (3 mm), made of high grade steel "Domex 460" or S 460 MC or equivalent	
Hook ø 50 mm; Hook height as per DIN standard, or optional to local standards	
Subframe made of IPN 180;	
Double twin door with middle lock	
Rollers with grease nipples ø 160 mm, made from either Polyamid or high grade steel	
Additional work safety lock for door opening, mounted on subframe	
Hooks for tarpaulin fixing welded all around the container	
Primered and coated as per your preference, available in many standard colors	
Additional ladder can be fixed on front side	
RFID chip, Branding and sticker options	
One year against manufacturing defects	



Focus Code: SH24ST1750 - 20